



RIDING MOWER & ATV OWNERS: CLEAR THICK GRASS AND TOUGH BRUSH WHILE YOU RIDE!

Got big areas to clear? Want to mow in ride-on comfort? Look no further than the Tow-Behind DR® FIELD and BRUSH MOWER.

Cutting a 44"-wide swath, this rugged mower is an easy haul for your ATV, riding mower or utility tractor. The articulating hitch can be set straight or offset to the left or right; 50%, 75% or 100% outside the path of your towing vehicle. An overhead valve engine ensures the swinging blades have the power to slice through woody material up to 2" in diameter. And a deep deck and open discharge chute keep you moving forward without clogging.

Hook up with a Tow-Behind model and enjoy the ride. It's the fastest way to take back your overgrown property.

BUILT WITH PRIDE
All DR FIELD and BRUSH MOWERS
are proudly made in the USA.



17 HP MODEL
SHOWN



13 HP MODEL

...clears tough weeds, brush and springy saplings in a single pass.

- Cuts 4-foot grass; 1-1/2"-thick saplings • 18"-diameter sealant-filled tires
- Electric-Starting • 442 lbs.

13 HP BRIGGS & STRATTON INTEK ENGINE (19.72 ft-lbs torque): Overhead valve, cast-iron cylinder sleeve, 2.5-gallon fuel tank with fuel gauge, anti-vibration system, spin-on oil filter, full-pressure oil lubrication, 2-year engine warranty for residential use; 1 year for commercial use.

17 HP MODEL

...more power for extra tough jobs and for faster cutting action.

- Cuts 6-foot grass; 2"-thick saplings • 18"-diameter sealant-filled tires
- Electric-Starting • 465 lbs.

17 HP KAWASAKI FH541V KAI V-TWIN ENGINE (29.7 ft-lbs torque): Overhead valve, cast-iron cylinder sleeves, 2.5-gallon fuel tank with fuel gauge, anti-vibration system, spin-on oil filter, full-pressure oil lubrication, pulse-type fuel pump, in-line fuel filter, 2-year engine warranty for residential or commercial use.

ARTICULATING OUTRIGGER™ HITCH allows the mower to be offset to either side, so the towing vehicle can drive in the clear while the mower takes down the tough stuff.

44"-WIDE CUT Mow up to 2 acres of open meadow or pasture per hour.

SWINGING BRUSH BLADES Replaceable, Pro-Tek™ swinging blades pivot when they hit an immovable object. This protects the blade spindle and the engine from damage.

WELDED MOWING DECK Made of 1/8"-thick steel (11-gauge) for maximum strength and longevity in rugged, field mowing conditions. The deck's funnel shape provides extra strength and rigidity, while creating a non-clogging discharge out the back.

SEALANT-FILLED TIRES If a tire is punctured by a sharp stick, stubble or rock, a sealant instantly plugs the hole so you can keep working.

ELECTRIC CLUTCH The electric clutch enables you to engage and disengage the blade with the push or pull of a button located on the remote control box. Far easier to engage/disengage, no maintenance, and far greater durability than idler-belt clutches.

GET ATTACHED TO MOST ANY TOWING VEHICLE

Our unique Versa-Hitch™ makes it easy to hook up to ATVs, riding mowers and tractors with a pin hitch, regardless of the height of the vehicle hitch.

TOWING VEHICLES

ATVs, UTVs, utility tractors, lawn and garden tractors. (Tractors: minimum 14 HP and/or 400 lbs.)

PROTECTED BY A 2-YEAR WARRANTY against defects in materials and workmanship in residential use; 90 days commercial use.