



## TAKE A SEAT. NOW YOU CAN TILL WHILE YOU RIDE! AND HAVE THE GARDEN YOU ALWAYS DREAMED OF.

Because you tow the DR® ROTO-HOG™ POWER TILLER, the full power of its overhead valve Briggs & Stratton engine (8.75 ft/lbs torque) is dedicated to the real task at hand...tilling the soil. Unlike walk-behind tillers, no engine power is wasted moving this tiller forward. Your towing vehicle does that, and with its weight, actually helps hold the tiller back.

The result is the DR ROTO-HOG™ POWER TILLER will till unbroken ground, including tough sod, in a fraction of the time required by any walk-behind tiller.

Even better, it is twice as wide as most ordinary tillers and applies twice the tine coverage. That means faster, more thorough tilling, with none of the strain associated with tillers that require sheer strength to control them. Instead, you just ride and relax.



**BUILT WITH PRIDE**  
All DR ROTO-HOG™ POWER TILLERS  
are proudly made in the USA.

### REMOTE CONTROL

The Remote Control rides with you on your towing vehicle and connects to the tiller with a heavy-duty cable. Use it to raise and lower the tines, and to operate the optional Powered Spreader and Culti-packer Attachments. On the electric-start model, you can start and stop the engine with the Remote Control.

### POWERED DEPTH CONTROL

You can raise or lower the tilling depth from 1" to 7.5" with the push of a button, remotely from your towing vehicle. You can also raise the tines completely off the ground, for easy turning or transport.

### SMOOTH-TRAK™ HITCH

Spring-loaded hitch absorbs shocks so that forward motion from the tiller is not transmitted directly to the towing vehicle and operator, for smoother, easier operation.

### SINGLE POINT PIN HITCH

The tiller attaches quickly and easily, without lifting, to any pin-type hitch. Just use the Remote Control to raise/lower the tiller's tongue to the height of your vehicle's hitch.

### POWERFUL OHV BRIGGS & STRATTON ENGINE

The DR ROTO-HOG™ POWER TILLER uses a powerful Overhead Valve Briggs & Stratton engine with 8.75 ft/lbs of torque. The engine features a cast-iron cylinder sleeve for extended life.

### EXTRA HEAVY-DUTY CONSTRUCTION

The frame is constructed of 1.5" square, 12-gauge steel. The tine shroud is made of 13-gauge steel. The heavy-duty tine shaft ball bearings make this unit rugged enough to break never-tilled, even compacted soil.

### PROTECTED BY A 2-YEAR WARRANTY

All DR ROTO-HOG™ POWER TILLERS (including the engine) are guaranteed to be free from defects in materials and workmanship for 2 years in residential use; 90 days in commercial use.

### POWERED SPREADER ATTACHMENT

This spreader can be turned on and off remotely, from your towing vehicle. Carries up to 125 lbs. of fertilizer, lime, or seed.

### AGRICULTURAL-STYLE CULTI-PACKER ATTACHMENT

Use this attachment after seeding to maximize seed-to-soil contact and dramatically increase germination rates. Excellent for planting cover crops, grass seed, and food plots.