



**PRO 35 SERIES
RECIPROCATING AIR COMPRESSOR
BID SPECIFICATION
REVISED: April 17, 2019**

Type:	Vanair® PRO 35 Series. New and in current production.
Compressor:	Reciprocating type. 2 cylinders, single stage, splash lubricated, steel braided discharge line, automatic throttle control with unloader valve.
Compressor Capacity:	35 CFM at up to 175 PSIG
Engine:	Single cylinder, electric or pull start, gasoline engine, Honda® 11HP or Kohler® 14HP
Fuel Capacity:	1.75 gallon
Air Storage Tank:	Options for 30 gallon, or remote air tank. ASME/CRN certification on appropriately sized tanks. Unit to include pressure gauge, ball valve, pressure relief valve, and condensation drain.
Weight:	Dry weight (Lbs.): 387 - 475 depending on platform.
Dimensions:	42L x 18W x 23H (In.) on remote mount air storage models 44L x 19W x 38H (In.) on 30 gallon air storage models
Drive System:	Classic V-belt drive system
Metal and Tanks:	Fully powder-coated belt guard, 3/16" plate steel main frame, full service access
Warranty:	The air compressor shall be warranted for 2 years when following the prescribed maintenance schedule. This warranty does not cover damage caused by accident, misuse, or negligence. If the unit is disassembled the warranty is void.
Service Centers:	Manufacturer MUST have factory authorized service centers located in each state of the United States of America and Canadian provinces.
Options:	Remote Air Tanks Vibration Isolators Maintenance Kits Batteries